

MOTOR OIL



PENTO HIGH PERFORMANCE 5W-30

Fully Synthetic Fuel Economy Engine Oil

DESCRIPTION

5W-30 Pento High Performance is a fully synthetic high performance engine oil, developed for the most recent vehicles with extended oil service intervals. Pento HP can be used in all gasoline and diesel engines containing turbochargers as well as non-turbocharged vehicles requiring 5W-30.

SIZE	PART NUMBER	GTIN-13
1 Liter	8043107	4008849115233
5 Liter	8043206	4008849155239
210 Liter	8043305	N/A

PRODUCT ATTRIBUTES

Appearance	Amber & Clear
Density at 15°C	852 kg/m ³
Density at 20°C	849 kg/m ³
Kinematic Viscosity at 100°C	12.3 mm ² /s
Kinematic Viscosity at 40°C	73 mm ² /s
Viscosity Index	167
Dynamic Viscosity at -30°C	5900 mPa*s
Pour Point	-36°C/-32.8°F
Flash Point	220°C/428°F

OE REFERENCE NUMBERS

Make	Reference Number
Audi/Volkswagen	ZVW 352 167
BMW	83 21 0 144 450
BMW	83 21 0 144 452
BMW	07 51 0 017 866
Mini	83 21 0 144 468
Mercedes Benz	000 989 78 01
Mercedes Benz	000 989 83 01

APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
Audi/Volkswagen	502.00, 505.00
BMW	LL-01
Mercedes Benz	229.5
Opel/GM	GM-LL-B-025
ACEA	A3/B4
API	SL/CF

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional installer upon request.

© 2010 CRP Industries Inc. Pentosin is a trade name of Deutsche-Pentosin Werke. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions or manufacturing changes.

PENTOHP5W30-011510



CONTITECH REIN AUTOMOTIVE PENTOSIN
OE quality brands for import applications.